



AUTOMATIC TRANSMISSION FLUID DEXRON III / MERCON

TECHNICAL DATA

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, LUBRISTRONG AUTOMATIC TRANSMISSION FLUID DEXRON III / MERCON resists oxidation, rust, corrosion, foaming, and varnish. The comprehensive additive package is designed for excellent oxidation stability and thermal resistance as well as excellent friction modification properties. LUBRISTRONG AUTOMATIC TRANSMISSION FLUID DEXRON III / MERCON is a multipurpose automatic transmission lubricant recommended where a Dexron-III/Mercon fluid is required. This multi-functional transmission fluid is suitable for power steering units where the manufacturer recommends a Dexron III or Mercon fluid for its systems. Other manufacturer suggested applications include mobile hydraulic and industrial systems, and rotary air compressors under specified service requirements.

SPECIFICATIONS

<u>PARAMETER</u>	<u>TYPICAL</u>
Appearance	Red, dyed
Viscosity cSt @ 40°C	36.1
Viscosity cSt @ 100°C	7.35
Viscosity Index	175
Pour Point, °F	-46
Flash Point, °F	362

Suitable for use where the following fluids are recommended:

GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H
Ford MERCON®, M2C-33, M2C-138-CJ, M2C-166-H or Type A
Detroit Diesel Allison C-3, C-4
Caterpillar TO-2

PRODUCT CODE: LSATFDM

REVISION DATE: Feb/2015



Made in USA